




## Sanitary Assembly

This probe assembly is specifically designed for the food, dairy, beverage, pharmaceutical, biotech, chemical, toiletries and cosmetic industries. Fitting sizes range from 1/2" to 3". The assembly meets FDA requirements in and around washdown areas. The sensing is based temperature on the customer specified sensor requirements. Available in RTD's and thermocouple types. A white Polypropylene head is standard, however other options Transmitters are also available. available if required.

### **ORDERING INFORMATION**



#### Box 8: Sensor Type

Code	<b>Description</b>
K	T/C Type K
J	T/C Type J
Т	T/C Type T
Α	RTD, $100\Omega$ ,
	.00385 DIN
(other	s available)

#### **Box 9: Configuration**

Code	Description
G	Single, Grounded
U	Single, Ungrounded
D	Dual, Grounded
N	Dual, Ung., Seperate
C	Dual, Ung., Common
W	RTD 2 wire, single
X	RTD 3 wire, single
Υ	RTD 4 wire, single
V	RTD 4 wire, dual

RTD 6 wire, dual

#### Available Accessories

Adapters Clamps Fittings Gaskets Reducers Valves

Box 10,11,12: Probe Length {A}

Whole Inc	ches - Box 10,11
Code	Description
	Whole Inches,
	(01 to 24)

# Fractional Length - Box 12 <u>Code</u> Description A .000 (no fraction) B .250 (1/4) C .500 (1/2) D .750 (3/4)

Ex: An input of {08C} equals a probe length of 81/2 inches.

Special

#### Box 15: Head Options:

Code	Description
Α	HSCA,
	Screw Cover Alum.
F	HFCA,
	Cast Alum. Flip Top
Н	HSCS,
	Stainless Screw Cover
N	NO HEAD
P	HSPB,
	PVC Black Screw Cover
R	HFPB,
	PVC Black Flip Top
Т	*HSPW,
	PVC White Screw Cover
W	*HFPW,
	PVC White Flip Top
	(Standard)
	*FDA Compliant

#### Box 13, 14: Triclover Size

Code	Material & Measurement
4A	SS304, 1/2" & 3/4"
4B	SS304, 1" & 1 1/2"
4C	SS304, 2"
4D	SS304, 2 1/2"
4E	SS304, 3"
6A	SS316, 1/2" & 3/4"
6B	SS316, 1" & 1 1/2"
6C	SS316, 2"
6D	SS316, 2 1/2"
6E	SS316, 3"

